

TRACKSHOT PROMOTIONS  
BONE STOCK DEMO RULES 2018

1. Front Bumper: Stock bumper must be stock mounted. Shocks can be collapsed or you can hard nose it, no extra metal. 4x4 hollow square tube ¼ inch thick ends opened
2. You may weld top seams, A arms forward with one pass ½" wide.
3. Tires: Must be OEM type tires. No valve stem protectors or bead locks allowed.
4. Limited to two ¾" all thread in front hood and two ¾" all thread in trunk hood. Four double wrapped pieces of #9 wire per hood is allowed.
5. Any drive train is allowed. Motors must be rubber mounted in stock position. Two chains from head to frame.
6. Headers are allowed.
7. Drivers door can be welded shut with four 6"x4" 1/8" plates.
8. No reinforcing of any kind.
9. Rear ends must be stock.
10. You may replace body bolts with ¾" bolts. Must have 1" spacer at firewall mounts. Can not go all the way through the frame.
11. Pre-bending is allowed. Body creasing is not allowed.
12. Drivers cage can be a 4 point cage with 2 down tubes on driver's side and can be connected to top of the frame.
13. Sliding drive shafts allowed.
14. No suspension modifications.
15. Front windshield bar is mandatory. Bolted 3" on roof and to window seam on bottom.
16. No gray areas. Follow the rules. This is stock. If you spend more than 4 days on this, you are overbuilt.

**OFFICIALS HAVE FINAL SAY ON EVERYTHING!!!!**